

SILTEC

BIOSOLV

PLANT-BASED

ECO RESPONSIBLE
Charter

GREEN RANGE

NOT DERIVED FROM
ORGANIC FARMING

THE PROFESSIONAL RANGE

CLEANS - REMOVES GREASE - REMOVES TAR - LOOSENS - LUBRICATES - DEOXIDISES

DESCRIPTION

BIOSOLV was specially developed to replace hydrocarbon solvents and other solvents made from petroleum products. BIOSOLV is a plant-based formula consistent with an eco-responsible ethic.

BIOSOLV is a 'green' solvent derived from plant chemistry, which makes its formula easily biodegradable and ecological.

BIOSOLV is fireproof.

BIOSOLV is compatible with all materials.

BIOSOLV completely protects the user. It does not contain any VOCs and is non-irritating.

BIOSOLV is emulsionable and can be used diluted.

BIOSOLV is used with a parts washer (mobile washer or grease-removing washer) at 50%. (Eg: 50L of BIOSOLV 50 litres of hard water for the bulk formula).

Cleaning – Removing grease

- Mechanical parts
- Grease - Cooked grease
- Adhesives
- Oils – Lubricants
- Tar
- Sludge
- Asphalt
- Glues
- Putty – Plaster
- Resins
- Fresh paint

USE

Thoroughly unjams and loosens rusted parts, jammed mechanisms and even the most corroded and rusted nuts and bolts. Separates plastic and metal parts, frees engaged parts and all blocked mechanisms.

Lubricates: with excellent anti-friction properties, it frees brake cables, locks, bike and motorcycle chains, handles, hinges and all friction parts. Eliminates squeaking, protects and stops humidity: chases humidity, deposits a protective film on all surfaces treated, prevents and blocks rust, prevents corrosion, chases humidity from electrical and electronic circuits: re-establishes contact, isolates metallic surfaces.

Removes grease: dissolves all types of grease, asphalt, and tar on all media, suitable for removing grease from equipment of all types.

FIELDS OF APPLICATION

MECHANICAL INDUSTRY - AUTOMOBILES – BOATS – BICYCLES – MOTORCYCLES - GO-KARTING

INSTRUCTIONS

BIOSOLV aerosol – spray: Apply with small successive sprays on the surface to be treated. Leave for a few minutes and remove any excess product using a cloth.

BIOSOLV in bulk: pure or diluted, soak in a grease extraction tank, with a brush, with a sponge; to protect parts, dry using a blower or wipe with a cloth. To restore the original appearance, rinse with clear water.

BIOSOLV wipes: Unfold the wipe completely and apply the product evenly on the surface to be cleaned.

WARNINGS

For professional use. Consult the SDS (on request only).

The information in our brochures, letters, reviews and reports is provided to advise you especially regarding testing that has been carried out, with an ongoing concern for objectivity and without any commitment on our part.

PACKAGING

72 wipes per package
Cardboard box 6 packages
Cardboard box 12 x 500 ml
(refillable aerosol spray)
Cardboard box 12 x 400 ml (aerosol)
Cardboard box 4 x 5 L
Barrels 30L-60L-210L



Nonfood Compounds
Program Listed (A8)
(Registration #145887)



www.siltec-actalys.com

ACTALYS - ZA DU HAUT DES TAPPES - BP 70065 - 54310 HOMECOURT - FRANCE
TEL +33 3 82 20 67 50 - FAX +33 9 70 61 29 66 - [SILTEC-ACTALYS@ORANGE.FR](mailto:siltec-actalys@orange.fr)